BLACK DEVIL



APPLICATION:

- Suction and discharge hose for the transfer of hot tar and asphalt
- A highly reliable transfer hose between trucks, rail cars or storage tanks
- Full vacuum rating

TEMPERATURE RANGE:

- -40°F to +350°F (400°F intermittent)
- -40°C to +175°C (205°C intermittent)

BURST PRESSURE:

■ Minimum 4:1

MATERIAL TUBE:

 Extruded, smooth special high-grade and heat resistant NBR rubber compound

REINFORCEMENTS:

- Multiple braids of high-tensile textile
- Dual helix wire for stability and added flexibility

MATERIAL COVER:

- Black, smooth neoprene (CR) rubber
- Exceptional resistance to abrasion, heat and oil
- Excellent weather and ozone resistance

BRANDING:

- Red longitudinal mylar stripe: GOODALL® BLACK DEVIL • TAR & ASPHALT 150 PSI
- Embossed stripe: N2586 •
 BLACK DEVIL TAR &
 ASPHALT SERVICE
 ONLY 150 PSI MAX WP
 350F MAX TEMP 400F
 - INTERMITTENT 10001
 * REFER TO INDUSTRY
 RECOMMENDATIONS FOR
 PROPER CARE
 - * Year of Manufacture

STANDARD LENGTHS:

■ 100 feet, 30.5 meters

BLACK DEVIL

| ID | | OD | | maximum working pressure | | vacuum | minimum bend radius | | weight | |
|-------|-------|-------|------|--------------------------|-----|--------|---------------------|------|--------|---------|
| mm | inch | mm | inch | bar | psi | hg | mm | inch | kg/m | lb./ft. |
| 51.0 | 2 | 69.1 | 2.72 | 10 | 150 | 28 | 190.5 | 7.5 | 2.29 | 1.54 |
| 63.0 | 2 1/2 | 83.6 | 3.29 | 10 | 150 | 28 | 254.0 | 10.0 | 3.18 | 2.14 |
| 76.0 | 3 | 95.0 | 3.74 | 10 | 150 | 28 | 292.1 | 11.5 | 3.63 | 2.44 |
| 102.0 | 4 | 122.7 | 4.83 | 10 | 150 | 28 | 546.1 | 21.5 | 5.00 | 3.36 |

All data at 68° F / 20° C

BLACK DEVIL • TAR & ASPHALT 150 PSI

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer/s/user/s method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.