



## BLASTALL SANDBLAST

according ISO 3861:2005

### APPLICATION :

- Heavy-duty hose for sandblasting and transfer applications in shipyards, construction, steel mills or other high demanding service.
- The rubber tube provides a great resistance to sand and other abrasive materials and dissipates static electrical charge for operator safety.
- Kink resistant

### TEMPERATURE RANGE :

- -40°C to +70°C
- -40°F to +158°F

### BURST PRESSURE:

- 3:1

### MATERIAL TUBE :

- Black NR/SBR rubber compound
- High abrasion resistance: 50mm<sup>3</sup> according ISO 4649:2010
- Electrically conductive  $R < 2 \times 10^3 \Omega$

### REINFORCEMENTS :

- Multiple high tensile spiral-plied textile cords

### MATERIAL COVER :

- Smooth SBR/NR rubber compound, black, electrically conductive  $R < 2 \times 10^3 \Omega$
- Wrapped finish impression
- Abrasion, weather & ozone resistant

### BRANDING:

- White longitudinal Mylar stripe : GOODALL BLASTALL - SANDBLAST 10 BAR – 150 PSI
- Embossed strip : GOODALL BLASTALL – 150PSI (10BAR)

### STANDARD LENGTHS:

- 30,5 or 61 meter
- 100 or 200ft

### BLASTALL SANDBLAST

ID		OD		maximum working pressure		minimum burst pressure		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb./ft.
19	3/4"	38,0	1,50	10,0	150	30	450	190	7,5	1,03	0,69
25,4	1"	48,0	1,89	10,0	150	30	450	254	10,0	1,53	1,03
32	1 1/4"	55,0	2,17	10,0	150	30	450	320	12,6	1,86	1,28
38	1 1/2"	60,0	2,36	10,0	150	30	450	380	15,0	2,03	1,36
50,8	2"	73,0	2,87	10,0	150	30	450	510	20,0	2,47	1,66

Size tolerances according ISO1307

All data at 68°F/20°C

**Goodall** BLASTALL • SANDBLAST 10 BAR - 150 PSI

**Goodall**

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.

