

## DESERT



### APPLICATION :

- Hose for conveying hot air from blower or compressor to tanks on bulk dry material carriers

### TEMPERATURE RANGE :

- -20°F to +325°F
- -29°C to +163°C

### BURST PRESSURE:

- 3:1

### MATERIAL TUBE :

- Black, heat resistant EPDM rubber compound

### REINFORCEMENTS :

- Multiple spiral-ply synthetic fabric
- Steel wire helix

### MATERIAL COVER :

- Black, heat resistant EPDM rubber compound
- Good abrasion, weather & ozone resistant

### BRANDING:

- White spiral Mylar stripe : GOODALL DESERT - HOT AIR BLOWER 100 PSI 325°F
- Embossed strip : GOODALL DESERT 100 PSI (7 BAR) 325°F (163°C) MAX TEMP

### STANDARD LENGTHS:

- 100 feet
- 30,5 meter

## DESERT

ID		OD		maximum working pressure		minimum burst pressure		vacuum HG		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	mm	inch	kg/m	lb./ft.
50,8	2	64,8	2,55	7	100	28	400	737	29	127	5	1,82	1,22
76,2	3	90,2	3,55	7	100	28	400	737	29	178	7	2,87	1,93
101,6	4	117,1	4,61	7	100	28	400	737	29	254	10	3,94	2,65

All data at 68°F/20°C



All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.