



MILKO SD LITE

MEETS FDA, BFR AND EC 1935/2004

APPLICATION :

- Highly flexible suction and delivery hose for filling and discharging milk tankers
- Also suitable for conveying alcoholic and non-alcoholic beverages products
- Light and easy to handle
- Complying to multiple international regulations
- Easy to clean because of smooth tube
- ADI (Animal Derived Ingredient) Free
- Non marking abrasion resistant cover
- Improved ergonomics for operators
- Superior kink and crush resistance

TEMPERATURE RANGE :

- -31°F to 176°F
 - -35°C to 80°C
- Open end steam cleaning up to 130°C/266°F (max 30 minutes)

BURST PRESSURE:

- Minimum 18 bar / 270 psi

MATERIAL TUBE :

- Extruded, smooth, white NR rubber
- Complies to FDA, Bfr and EC 1935/2004 regulations
- ADI (Animal Derived Ingredient) free
- Excellent resistance to the most common cleaning agents

REINFORCEMENTS :

- Spiral-plyed high tensile synthetic fabric
- Plastic helix

MATERIAL COVER :

- Blue NR rubber compound
- Smooth, non-marking cover
- Heat, abrasion, weather & ozone resistant

BRANDING:

- White longitudinal Mylar stripe : GOODALL MILKO SD LITE - FOOD 6 BAR - 90
- Embossed strip : GOODALL MILKO SD LITE - 90PSI (6BAR) - quarter/year

STANDARD LENGTHS:

- 40 meter
- 131ft

MILKO SD LITE

ID		OD		maximum working pressure		minimum burst pressure		vacuum	minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	%	mm	inch	kg/m	lb./ft.
38.0	1 1/2"	50	1.97	6	90	18	270	90	76	3.0	1.30	0.87
51.0	2"	63	2.48	6	90	18	270	90	102	4.0	1.80	1.21
53.0	2 09"	65	2.56	6	90	18	270	90	105	4.1	1.85	1.24
63.0	2 1/2"	75	2.95	6	90	18	270	90	126	5.0	2.00	1.34
76.2	3"	90	3.54	6	90	18	270	90	452	17.8	2.75	1.85

Size tolerances according ISO1307