



NITRO PURPLE

APPLICATION :

- For use in nitrogen service to purge lines in refineries, petrochemical, and general industries.

TEMPERATURE RANGE :

- -20°F to +150°F
- -29°C to +65°C

BURST PRESSURE:

- 4:1

MATERIAL TUBE :

- Black thermoplastic PVC/ NBR compound
- RMA Class A

REINFORCEMENTS :

- Multiple spiral high tensile polyester

MATERIAL COVER :

- Purple thermoplastic PVC/ NBR compound, abrasion and weather resistant
- RMA Class A

BRANDING:

- GOODALL NITRO . Nitrogen gas 300 PSI WP 3/4" Made in Canada (manufacturing quarter and year)

STANDARD LENGTHS:

- 50 feet reels
- 15,24 meter reels

NITRO BLUE

ID		OD		maximum working pressure		minimum burst pressure		minimum bend radius		weight	
NB	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb./ft.
DN19	3/4"	30,2	1,19	20	300	80	1200	178,0	7,0	0,6	0,4

All data at 68°F/20°C

Goodall NITRO • NITROGEN GAS 300 PSI WP 3/4" MADE IN CANADA

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.