



## NUTRALON

MEETS 3A (18-03 CLASS II), USDA, FDA, BFR AND EC 1935/2004

REACH COMPLIANT

### APPLICATION :

- Food suction and discharge hose for transfer of milk products, animal fat, vegetable oil, fruit juices and other food products
- Suitable for alcohol 96% at 40°C / 104°F (intermittent at 80°C / 208°F - 30 minutes)
- For in-plant service and wash-down service
- Braided construction has excellent flexibility
- Complying to multiple international regulations
- Easy to clean because of smooth tube
- ADI (Animal Derived Ingredient) Free
- Phthalate Free
- Non marking abrasion resistant cover

### TEMPERATURE RANGE :

- -22 °F to 212 °F
- -30 °C to 100 °C
- Open end steam cleaning up to 130°C/266°F (max 20 minutes)

### BURST PRESSURE:

- Minimum 4:1

### MATERIAL TUBE :

- Extruded, smooth white nitrile rubber
- Non-contaminating formulation
- Complies to the most stringent international food regulations
- Excellent resistance to fatty foods like animal fats and vegetable oils
- Does not propagate bacteria growth
- Excellent resistance to the most common cleaning agents

### REINFORCEMENTS :

- Multiple high tensile textile braids

### MATERIAL COVER :

- Blue, CR blend rubber
- Superior abrasion, weather and ozone resistance
- Non marking cover
- Resistant to vegetable oils and animal fats

### BRANDING:

- White and blue spiral stripe: GOODALL NUTRALON • FOOD 17 BAR – 250 PSI
- Embossed stripe: N2920 • NUTRALON • DN \* • 17 BAR-250 PSI • MEETS FDA, BFR, EC 1935/2004, 3A 18.3 CLASSII & USDA REQUIREMENTS • MFR C-Y-M • MADE IN CANADA 10001

### STANDARD LENGTHS:

- 40 meters, 131.2 feet

## NUTRALON

ID		OD		maximum working pressure		minimum burst pressure		vacuum	minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	%	mm	inch	kg/m	lb./ft.
13.0	1/2	23	0.91	17	250	68	1000	50	90.0	3.5	0.57	0.38
19.0	3/4	31	1.22	17	250	68	1000	50	125.0	4.9	0.67	0.45
25.0	1	37	1.46	17	250	68	1000	50	150.0	5.9	0.80	0.54

All data at 68°F/20°C

**Goodall** NUTRALON • FOOD 17 BAR - 250 PSI



All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.