



VINTAGE

Meets FDA, 3A (18-03 CLASS III) and USDA Requirements

APPLICATION:

- Flexible suction and discharge hose for use in wineries, breweries and other food and beverage industries
- Tasteless and odorless tube with high temperature resistance for open end steam cleaning (max 30 minutes at 266°F/130°C)
- Extremely good bending radius
- Crush and kink resistant design

TEMPERATURE RANGE:

- -40°F to +230°F
- -40°C to +110°C

BURST PRESSURE:

- Minimum 4:1

MATERIAL TUBE:

- Smooth and seamless chlorobutyl (CIIR)
- Non-contaminating formulation

REINFORCEMENTS:

- Multiple braids of high-tensile textile reinforcement
- Dual monofilament helix

MATERIAL COVER:

- Grey, smooth EPDM rubber
- Superior abrasion, weather and ozone resistance

BRANDING:

- Blue longitudinal mylar stripe: GOODALL • VINTAGE • FOOD 250 PSI
- Embossed stripe: N2450 • VINTAGE • 250 PSI MAX WP • MEETS FDA, 3A 18.0 CLASS III & USDA REQUIREMENTS • 10001 • * • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

STANDARD LENGTHS:

- 100 feet, 30.5 meters

VINTAGE

ID		OD		maximum working pressure		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	mm	inch	kg/m	lb./ft.
25.0	1	42.4	1.67	17	250	50.8	2.0	0.94	0.63
38.0	1 ½	55.6	2.19	17	250	76.2	3.0	1.32	0.89
51.0	2	68.3	2.69	17	250	127.0	5.0	1.86	1.25
76.0	3	97.5	3.84	17	250	228.6	9.0	3.15	2.12
102.0	4	127.0	5.00	17	250	457.2	18.0	4.24	2.85

All data at 68° F / 20° C

