



ELEPHANT HIDE PLUS

APPLICATION:

- Superior LPG transfer hose for demanding conditions
- Reinforced with corrosion resistant stainless steel braids
- Exceptional high abrasion resistant cover
- Designed specifically for tank truck service (MC330 and NC331)
- Ideal for trailer to storage use
- Approved to UL 21

TEMPERATURE RANGE:

- -40°F to +180°F
- -40°C to + 82°C

BURST PRESSURE:

- Minimum 5:1

MATERIAL TUBE:

- Smooth and seamless extruded nitrile (NBR)
- Developed specifically to resist tube cracking caused by the transfer of LPG

REINFORCEMENTS:

- Multiple braids of stainless steel reinforcement
- Single braid of high-tensile textile

MATERIAL COVER:

- Superior abrasion resistant proprietary neoprene (CR)
- Pin pricked
- Compounded to resist cover cracking from exposure to weather and ozone conditions

BRANDING:

- Yellow, black and blue spiral mylar stripe: GOODALL • ELEPHANT HIDE PLUS • LPG 350 PSI
- Embossed stripe: N2805 • ELEPHANT HIDE PLUS • MH8393 • LP GAS HOSE ISSUE NO E8073 • Q-Y • 350 PSI (2.4 Mpa) MAX WP • 10001 • REFER TO INDUSTRY RECOMMENDATIONS FOR PROPER CARE & MAINTENANCE

STANDARD LENGTHS:

- 100 feet, 30.5 meters

ELEPHANT HIDE PLUS

ID		OD		maximum working pressure		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	mm	inch	kg/m	lb./ft.
25.0	1	41.1	1.62	24	350	101.6	4.0	1.26	0.85
32.0	1 ¼	47.5	1.87	24	350	152.4	6.0	1.56	1.05
38.0	1 ½	53.8	2.12	24	350	190.5	7.5	1.85	1.24
51.0	2	68.6	2.70	24	350	228.6	9.0	2.71	1.82
76.0	3	98.6	3.88	24	350	457.2	18.0	5.18	3.48

All data at 68° F / 20° C



All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.