



JACKHAMMER ASSEMBLIES

Tested according ISO 1402

APPLICATION :

- Quality hose for air tool applications on construction sites
- Reliable and safe crimped steel 'Universal Coupling'

TEMPERATURE RANGE :

- -40°F to +203°F
- -40°C to + 95°C

BURST PRESSURE:

- 4:1

MATERIAL TUBE :

- Black, smooth EPDM rubber
- Extruded

REINFORCEMENTS :

- 4 spiral polyester yarn
- High tensile strength

MATERIAL COVER :

- Red EPDM rubber compound
- Extruded
- Heat, abrasion, weather and ozone resistant

BRANDING:

- GOODALL JACKHAMMER. 250PSI/17BAR WP (size) . MADE IN USA

COUPLINGS:

- Crimped 'Universal Coupling', plated malleable iron

STANDARD LENGTHS:

- 50ft
- 15,24 m

JACKHAMMER ASSEMBLIES

ID		OD		maximum working pressure		minimum burst pressure		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb./ft.
19	3/4"	29,21	1,15	17,2	250	69	1000	114,3	4,5	13,7	36,8

All data at 68°F/20°C

Goodall JACKHAMMER • 250PSI/17BAR WP 3/4" DN19 • MADE IN USA

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.

