



MULTI YELLOW

APPLICATION :

- Multipurpose hose for compressed air, water and aqueous solutions.
- Suitable for pneumatic tooling.
- Conductive tube
- Easy to handle and flexible even at cold temperatures

TEMPERATURE RANGE :

- -20°C to +70°C
- -4°F to 160°F

BURST PRESSURE:

- 3:1

MATERIAL TUBE :

- Black, smooth EPDM rubber
- Extruded
- Electrically conductive $R \leq 10^6 \Omega$

REINFORCEMENTS :

- Up to DN25 (1"): Polyester yarn, braided
- From DN32 (1 1/4") on: spirally-plied synthetic fabric
- High tensile strength

MATERIAL COVER :

- Yellow, smooth EPDM rubber compound
- From DN32 (1 1/4") on: wrapped finish
- High abrasion, weather and ozone resistance

BRANDING:

- GOODALL MULTI 20BAR WP (size) MAX.70°C Ω

STANDARD LENGTHS:

- Fixed coil lengths

MULTI YELLOW

ID		OD		maximum working pressure		minimum burst pressure		minimum bend radius		weight	
mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb./ft.
6	1/4"	13	0,51	20	300	60	900	50	2,0	0,14	0,09
10	3/8"	20	0,79	20	300	60	900	75	3,0	0,32	0,21
13	1/2"	23	0,91	20	300	60	900	100	4,0	0,38	0,26
16	5/8"	26	1,02	20	300	60	900	125	5,0	0,44	0,30
19	3/4"	29	1,14	20	300	60	900	155	6,2	0,51	0,34
25	1"	37	1,46	20	300	60	900	205	8,2	0,79	0,53
32	1 1/4"	44	1,73	20	300	60	900	255	10,2	0,94	0,63
38	1 1/2"	50	1,97	20	300	60	900	305	12,2	1,07	0,72
50	2"	66	2,6	20	300	60	900	405	16,2	1,80	1,21
75	3"	91	3,58	20	300	60	900	610	24,4	2,52	1,69

Size tolerances according ISO1307

All data at 68°F/20°C

Goodall MULTI 20 BAR WP DN 6 Max. 70°C Ω

All information contained on this datasheet is subject to change without prior notice. GOODALL MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the Goodall product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance and storage of hoses may result in the hose's failure to perform properly and may result in damage to property and/or serious injury. Goodall or any of its affiliates or subsidiaries shall not be subject to and disclaims any obligations or liabilities (including but not limited to all consequential, incidental and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.